APM System Quick Install Guide

DEOOKE

Introduction

This quick guide supports the version of apm-v3.7.10 and supports all subsequent versions until the document is replaced by a new edition.

Important Notices

We reserve the right to revise this guide, and/or make improvements or changes in the step (s) described in this document at any time without prior notice.

www.digitalframe0.com

Copyright ©EOOKE ELECTRON. All RIGHTS RESERVED.

EOOKE ELECTRON www.digitalframe0.com

1. Unzip and copy the "apm-v3.7.10.exe" to the desktop and double-click the icon to start the installation.



2. Click "Yes" to allow the APM application to be installed.



3. Click "OK" to go to next step



Note: The installer will automatically uninstall the old version of APM (if exits). Restart the computer and click the "apm-v3.7.10.exe" to start the installation again once the Uninstall is completed.



4. Select installation path.

ietup - apm		<u>2001</u> 3		2
Select Destination Location				
Where should apm be installed?			Ć	
Setup will install apm into the following folder.				
To continue, click Next. If you would like to select a dit	fferent folder	, click Bri	owse.	
D:\apm		Br	owse	Ī
At least 2,418.4 MB of free disk space is required.				
At least 2,418.4 MB of free disk space is required.	Nev		Can	cel

Note:

- 1. It is not recommended to change the default installation location of the apps.
- 2. If you want to install applications on a different drive, path or folder, please ensure that the installation path and folder are in English and do not contain any special characters & space. Don't install it in following folders as they contain spaces and brackets symbols "()".



5. Hit "Next" to start installation.







6. Restart the computer to complete the installation.



7. Click APM icon on the desktop or "mian.exe" from installation directory to open the APM console.



8. Click "Start Service" button on console dashboard to start APM system. The launching process will appear in the LOG viewer.



💷 АРМ — 🗆 🗙	💷 APM — 🗆 🗙
service Port detection Settings	service Port detection Settings
service	Port
Shutdown The current service is starting	emqx 1883 8883
1	nginx 80 19520
start Log printing function switch. The current statu	tomcat 8283
	mysql 3317
start Timed restart switch, the current status is off	Start detection
start Power on switch, current status is off	Using CATALINA_BASE: "/" Using CATALINA_HOWE: "/" Using CATALINA_HOWE: "/temp" Using JRE_HOWE: "/.java\jre" Using CLASSPATH: "/\bin\bootstra
	p.jar;/\bin\tomcat-juli.jar" spring!!

The launching process will appear in the LOG viewer.

9. Wait 1-2 minutes until the service to be started.

💷 АРМ				8 <u>1 - 1</u> 8.		Х
service	Port o	letection	Settings			
service		1	Currents	onico etar	tod	
sta	rt	Log print	Current s	ervice star switch. The	ted e current	statu
sta	rt	Timed re	estart switch	n, the curre	nt status	is off
sta	rt	Pow	ver on switch	, current s	tatus is o	off
						•

10. Portable Chrome browser will be launched automatically once the APM is started.



Note:

- 1. For Local area network, please click Next to complete the entire installation.
- 2. For Cloud installation, you can input your actual IP or domain name.
- 11. Click "Next" go to "Sever verification" step.





EOOKE ELECTRON www.digitalframe0.com

12. Enter user name "root" and password "root" to login to the APM system.



Appendix

If you encounter an error when launching the APM, you can use the repair tool to fix the problem.

Navigate to [Settings] and click [Repair Tool] button to go to repair folder.

APM - O	🗙 😵 DirectX Repair OL -	International	_		o x	
rvice Port detection Settings	Eile Jool Help					
ttings (effective after research	×			Check and	d Repair 🔻	
angeleneene alter restarty	Information					
	Status :					
	H File :					
save Web service IP	Progress :	Progress :				
	File paper	32bi+ file	Ranai é	Whit file	Ranai	
	XAPOFX1_0. dll	Sebit Hite	nepai	Abit Hite	hepai	
	XAPOFX1_1. dll					
	XAPOFX1_2. dll XAPOFX1_3 dll					
save Terminal communication	XAPOFX1_4. dll					
	XAPOFX1_5. dll					
	XAudio2_0. dll					
	XAudio2_1. dll XAudio2_2. dll					
	XAudi o2 3. dll					
Repair tool Used to fix exception	IS XAudi o2_4. dll					
	XAudi o2_5. dll				~	
	Microsoft Windows 10 Pr	o(10.0.19043.0) 64-bit				
Download and install this feature Windows will get the files that it needs from Windows Update and complete the installation.						
→ Skip this installation Your apps might not work correctly without this feature.						
Skip this installation Your apps might not work correctly without this feature. Tell me more about this feature						
Skip this installation Your apps might not work correctly without this feature. Iell me more about this feature Cance Cance Cance Cance Cance Cance Cance Canc	α				[
Skip this installation Your apps might not work correctly without this feature. Tell me more about this feature Cance Name E	e∎	Туре		S	ize [
Skip this installation Your apps might not work correctly without this feature. Tell me more about this feature Cance Name Data 00	a Date modified	Type		S	ize	
Skip this installation Your apps might not work correctly without this feature. Tell me more about this feature Cance Name Data 9	e Date modified 1/19/2022 5:33 PM	Type File folde	er.	s	[ize	
	a Date modified 1/19/2022 5:33 PM 1/10/2019 4:20 PM	Type File folde Applicati	er	S	ize 863	
	Date modified //19/2022 5:33 PM //10/2019 4:20 PM	Type File folde Applicati	er on	S	ize 863	

Note: For Windows 7 system, please click "DirectX Repair" to start. It will update "Net Framework" if your version is not up to date. For Windows 8 and 10, please click "DirectX_Repair_win8_win10" to start.

Please don't hesitate to contact support@digitalframe0.com if you are in need of assistance.

EOOKE ELECTRON www.digitalframe0.com